Specification

Title of the Invention

Equalizer Circuit and Equalizing Method

5   Background of the Invention

        The present invention relates to an equalizer
circuit and equalizing method and, more particularly, to
an equalizer circuit and equalizing method for
preventing waveform distortion and interference waves
10   (noise) in multipath fading.

        In data transmission of a high-speed radio ATM
(Asynchronous Transfer Mode) system for multimedia
mobile communication of 20 to 30 Mbps using a 5.2-GHz
band, an equalizing function is used to prevent data
15   quality degradation in multipath fading.

        A technique using this equalizing function has
been proposed by the present applicant/assignee. This
technique proposes a radio data communication terminal
for narrowband modulation system, in which a tap
20   coefficient for an equalizer is set after a frequency
offset value for operating a phase rotation means is
obtained using, e.g., a shortest preamble.

        As shown in Fig. 3, the equalizer circuit for
performing the above equalizing function comprises a
25   carrier sensor 6 for sensing the presence/absence of an
input carrier and an equalizer unit 7 for receiving an
output from the carrier sensor 6. The equalizer unit 7

is comprised of a memory unit 8, phase rotation unit 9, phase difference detector 10, average value detector 11, integrator 12, vector converter 13, transmission line characteristic estimating unit 14, a tap coefficient setting unit 15, and equalizer 16.

The carrier sensor 6 senses the presence/absence of a carrier in accordance with an RSSI (Received Signal Strength Indicator) signal Q representing the reception level from an RF (Radio Frequency) converter (not shown). The carrier sensor 6 then detects the start of a reception signal and outputs a carrier sense signal R to the equalizer unit 7 for a time interval from time when detecting the start of reception data to time when receiving a demodulation data end signal S of a one-pulse signal for stopping the equalizer unit 7.

The memory unit 8 receives a reception data signal P for an arbitrary period to control the output. The phase rotation unit 9 rotates the phase of the output signal from the memory unit 8 through a necessary angle. The phase difference detector 10 obtains the current angle and the angle of a PN (Pseudo Noise) code sequence obtained upon the lapse of one period. The phase difference detector 10 then obtains the difference between these two angles.

The average value detector 11 integrates the phase difference from the phase difference detector 10 a

predetermined number of times. The average value
detector 11 then divides the integrated value by the
predetermined number of times to obtain the average
value of the average phase difference per symbol. The
5   integrator 12 integrates the average value from the
average value detector 11 in units of symbols. The
vector converter 13 converts the output from the
integrator 12 into a real part amplitude value and an
imaginary part amplitude value. The vector converter 13
10   outputs these amplitude values to the phase rotation
unit 9.

        The transmission line characteristic
estimating unit 14 obtains the transmission line
characteristics of the one-period PN code sequence for a
15   preamble period using the signal obtained upon phase
rotation in the phase rotation unit 9. The tap
coefficient setting unit 15 obtains a tap coefficient
necessary for the equalizer 16 in accordance with the
transmission line characteristics obtained by the
20   transmission line characteristic estimating unit 14.
The tap coefficient setting unit 15 then sets the tap
coefficient in the equalizer 16. The equalizer 16
equalizes the output from the phase rotation unit 9
using a filter having the tap coefficient set by the tap
25   coefficient setting unit 15. The equalizer 16 outputs a
demodulation data signal U. Reception processing is
performed using this demodulation data signal U.

Figs. 4A to 4F show the reception timings of a conventional phase shifter circuit shown in Fig. 3. In this case, the inactive interval of the reception data signal P is long.

5　　　The carrier sensor 6 determines the presence/absence of a carrier in accordance with the RSSI signal Q from the RF converter (Fig. 4B). The carrier sensor 6 then outputs the carrier sense signal R representing the start of the reception data signal P to

10　the equalizer unit 7 (Figs. 4A and 4C). Upon detecting the start of the reception data signal P, the equalizer unit 7 detects the frequency offset, estimates the transmission line characteristics, and sets the tap coefficient.

15　　　The equalizer 16 stores the preamble signal having the repeated PN code in the memory unit 8 and performs processing for a period of various initial settings (Fig. 4E) and has a delay accordingly. Upon completion of various initial settings in the equalizer

20　16, the demodulation data signal U is output (Fig. 4G). Upon completion of demodulation, the demodulation data end signal S is output to the carrier sensor 6 (Fig. 4F). At this time, the equalizer unit 7 is always operating in response to a system clock signal T (Fig. 4D) and

25　therefore consumes power. In addition, a long inactive interval decreases the information bit rate.

　　　Figs. 5A to 5G show the reception timings of

the conventional phase shifter circuit shown in Fig. 3. This exemplifies a short inactive interval of the reception data signal P.

The carrier sensor 6 determines the
5   presence/absence of a carrier in accordance with the RSSI signal Q from the RF converter (Fig. 5B) and outputs the carrier sense signal R representing the start of the reception data signal P to the equalizer unit 7 (Figs. 5A and 5C). The equalizer unit 7 detects
10 a frequency offset, estimates the transmission line characteristics, and sets the tap coefficient upon detecting the start of the reception data signal P.

The equalizer 16 stores the preamble signal having the repeated PN code in the memory unit 8 and
15 performs processing for a period of various initial settings (Fig. 5E) and has a delay accordingly. Upon completion of various initial settings in the equalizer 16, the demodulation data signal U is output (Fig. 5G). Upon completion of demodulation, the demodulation data
20 end signal S is output to the carrier sensor 6 (Fig. 5F). At this time, the equalizer unit 7 is always operating in response to a system clock signal T (Fig. 5D) and therefore consumes power.

Since the inactive interval of the reception
25 data signal P is short, a carrier detection signal β representing the leading edge of the carrier sense signal R cannot be detected upon receiving the next

frame during a carrier sense period α. Therefore, the
reception operation is performed every other frame, and
the demodulation data signal U cannot normally be output.

In the above conventional equalizer circuit, a
5 long inactive interval undesirably decreases the
information bit rate. When the next frame is received
during the processing period of the demodulation data
with a short inactive interval, the carrier sense signal
cannot be detected. Data is received every other frame,
10 resulting in a reception error. Since the equalizer
unit is always operating in response to the system clock
signal, wasteful power is undesirably consumed.

Summary of the Invention

It is an object of the present invention to
15 provide an equalizer circuit and equalizing method
capable of normally performing real-time processing even
upon receiving a continuous burst signal.

It is another object of the present invention
to provide an equalizer circuit and equalizing method
20 which can reduce power consumption.

In order to achieve the above object of the
present invention, there is provided an equalizer
circuit comprising carrier sensing means for sensing the
start of a reception signal on the basis of a signal
25 representing a reception level of the reception signal,
first and second equalizing means for equalizing the
reception signal, control means for alternately enabling

- 6 -

the first and second equalizing means every frame

reception in accordance with an output from the carrier

sensing means, and switching means for alternately

switching between outputs from the first and second

5   equalizing means every frame reception and outputting

the selected output as demodulation data.

Brief Description of the Drawings

Fig. 1 is a block diagram of an equalizer

circuit according to an embodiment of the present

10   invention;

Figs. 2A to 2N are timing charts showing

operation of switching two parallel equalizers according

to the embodiment shown in Fig. 1;

Fig. 3 is a block diagram of a conventional

15   equalizer circuit;

Figs. 4A to 4G are timing charts of

conventional operation for a long inactive interval; and

Figs. 5A to 5G are timing chats of

conventional operation for a short inactive interval.

20   Description of the Preferred Embodiment

The present invention will be described in

detail with reference to the accompanying drawings.

Fig. 1 shows an equalizer circuit according to

an embodiment of the present invention.   Referring to

25   Fig. 1, the equalizer circuit of this embodiment is

comprised of a carrier sensor 1 for detecting the

carrier of an input signal, a carrier sense controller 2

for receiving an output from the carrier sensor 1, gate circuits 3a and 3b for receiving an output from the carrier sense controller 2, an equalizer unit 4a for receiving a reception data signal A and outputs from the carrier sense controller 2 and gate circuit 3a, an equalizer unit 4b for receiving the reception data signal A and the outputs from the carrier sense controller 2 and gate circuit 3b, and a reception data switching unit 5 for receiving outputs from the equalizer units 4a and 4b and outputting a demodulation data signal M. Gate signals from the equalizer units 4a and 4b are output to the carrier sense controller 2.

The carrier sensor 1 detects the start of the reception data in accordance with an RSSI signal B from an RF converter 21 and outputs a signal representing this start to the carrier sense controller 2. The carrier sense controller 2 determines the start of reception data in accordance with a signal from the carrier sensor 1 and detects the end of carrier sensing on the basis of demodulation data gate signals J and K respectively from the equalizer units 4a and 4b.

At the start and end of carrier sensing, the carrier sense controller 2 generates active-high carrier sense signals C and D for low-power consumption and real-time processing every other frame. The carrier sense controller 2 outputs the carrier sense signal C to the gate circuit 3a and equalizer unit 4a and the

carrier sense signal D to the gate circuit 3b and equalizer unit 4b. The carrier sense signals C and D serve as enable signals for the equalizer units 4a and 4b.

5   The gate circuit 3a masks a system clock signal E and the carrier sense signal C and outputs an active-high clock gate signal F to the equalizer unit 4a. The gate circuit 3b masks the system clock signal E and the carrier sense signal D and outputs an active-high

10   clock gate signal G to the equalizer unit 4b.

          The equalizer unit 4a detects the frequency offset, estimates the transmission line characteristics, and sets the tap coefficient upon receiving the carrier sense signal C. The equalizer unit 4a outputs the

15   demodulation data gate signal J and the demodulation data signal H to the reception data switching unit 5 upon initial setting of an internal equalizer 41a.

          The equalizer unit 4b detects the frequency offset, estimates the transmission line characteristics,

20   and sets the tap coefficient upon receiving the carrier sense signal D. The equalizer unit 4b outputs the demodulation data gate signal K and the demodulation data signal L to the reception data switching unit 5 upon initial setting of an internal equalizer 41b.

25   The reception data switching unit 5 alternately receives the demodulation data gate signal J from the equalizer unit 4a and the demodulation data

gate signal K from the equalizer unit 4b. The reception

data switching unit 5 switches (selects) between the

demodulation data signal H from the equalizer unit 4a

and the demodulation data signal L from the equalizer

5   unit 4b in response to the demodulation data gate

signals J and K and outputs the selected demodulation

data signal as the demodulation data signal M.

Reception processing is performed in accordance with the

demodulation data signal M from the reception data

10   switching unit 5.

Figs. 2A to 2N show the switching operation

for the two parallel equalizers shown in Fig. 1. The

reception data signal A is made up of preamble signals

for performing various training operations and

15   information data, as shown in Fig. 2A.

The preamble signals are received by repeating

a PN code for a predetermined period. The carrier

sensor 6 determines the presence/absence of a carrier in

accordance with the RSSI signal B from the RF converter

20   21 (Fig. 2B). The carrier sensor 6 then outputs the

carrier sense signals C and D representing the start of

the reception data signal A to the gate circuits 3a and

3b and equalizer units 4a and 4b (Figs. 2C and 2H).

Upon outputting the carrier sense signals C and D from

25   the carrier sense controller 2, the equalizer units 4a

and 4b detect the frequency offset values, estimate the

transmission line characteristics, and set the tap

coefficients using a PN-code one-period signal.

The equalizer units 4a and 4b store the PN
codes in an internal memory 42a during the respective
initial setting periods (Figs. 2E and 2J) and has delays
5   accordingly. At the end of the demodulation data
signals H and L from the equalizer units 4a and 4b, the
carrier sense controller 2 stops outputting the carrier
sense signals C and D, as will be described later.

The operation of the gate circuits 3a and 3b,
10   equalizer units 4a and 4b, and reception data switching
unit 5 will now be described in detail below.

The gate circuits 3a and 3b control to gate
the system clock signal E using the carrier sense
signals C and D as gate signals (Figs. 2C, 2H, and 2N).
15   While receiving the carrier sense signals C and D, the
gate circuits 3a and 3b output the clock gate signals F
and G (Figs. 2D and 2I). While receiving the carrier
sense signals C and D, the equalizer units 4a and 4b
perform the above-mentioned processing using the
20   reception data signal A and clock gate signals F and G.
As a result of processing, the equalizer units 4a and 4b
output the demodulation data signals H and L to the
reception data switching unit 5 (Figs. 2H and 2L). At
the same time, the equalizer units 4a and 4b output the
25   demodulation data signals J and K synchronized with the
demodulation data signals H and L (Figs. 2F and 2K).

The reception data switching unit 5 selects

- 11 -

the demodulation data signal H or L in accordance with
the demodulation data gate signals J and K and outputs
the demodulation data signal M (Fig. 2M). At this time,
the carrier sensor 2 stops outputting the carrier sense

5   signals C and D upon receiving the demodulation data
gate signals J and K.

Since the equalizer units 4a and 4b construct
a parallel circuit, these equalizer units can
alternately be switched in real time to allow reception

10   processing even if the next frame is received during the
carrier sense period. Since the clock gate signals F
and G are supplied to the equalizer units 4a and 4b,
power consumption can be reduced.

According to the present invention, the two

15   parallel equalizers 41a and 41b in the equalizer units
4a and 4b are alternately switched every frame and
operate for reception during only the clock gate period,
thereby reducing the power consumption. Real-time
processing is allowed even with delays in initial

20   settings for the equalizers in the equalizer units 4a
and 4b.

The two parallel equalizers (equalizers in the
equalizer units 4a and 4b) are alternately switched
every frame reception. Even if a continuous burst

25   signal having a short inactive interval is input, normal
processing can be performed in real time. In addition,
since the equalizer units 4a and 4b operate for

reception during only the carrier sense period, power

consumption can be reduced.